

Datasheet		SOCKET	
<b>Product</b> V98/ V99		Country of Origin: The Netherlands	
<b>Article code</b>	V98	338003915	
	V99	338003910	
<b>Dimensions</b>			
<b>Description</b>			
<p>Base with two high reliable cage clamp spring (WAGO) terminals per relay contact  For solid and (fine) stranded wires up to 2.5 mm<sup>2</sup>  Quick connection by pressing the cage clamp with a flat-bladed screw driver and inserting the stripped wire  Suitable for D and D-U relays.</p>			
<b>Contact rating</b>	10 A (AC1)	IEC 947	
<b>Dielectric strength</b>	2500 V; 50 Hz; 1 min	IEC 255/ IEC 571	
<b>Protection category</b>	IP 20	IEC 529	
<b>Mounting</b>	V98 V99	panelmounting DIN rail	DIN EN 50022
<b>Max ambient temperature</b>	80 °C		
<b>Weight</b>	V98 V99	268 g 290 g	
<b>Wire diameter</b>	0.08 - 2.5 mm <sup>2</sup>		
<b>Material</b>	Polyamide 6.6 30 % glass	Class 2 according to NF F 16-101 and 102	
<b>Options</b>	Key possibility		
<b>Accessory</b>	Key receptacle A104		



P.O. Box 7023  
3502 KA Utrecht  
The Netherlands  
**T** +31 (0)30-288 13 11  
**F** +31 (0)30-289 88 16  
**E** sales@nieaf-smitt.nl  
**I** www.nieaf-smitt.nl