



# *1X50K2 Test Manual*

## *CB Trip & Close Module*

relay monitoring systems pty ltd

---

### **Advanced Protection Devices**



User Guide



Test Manual



Relay Software



μMATRIXwin



# 1X50K2 Test Manual

## Links to Other Documents

- Technical Bulletin: <http://www.rmspl.com.au/handbook/1x30.pdf>
- User Guide: [http://www.rmspl.com.au/userguide/1x30\\_user\\_guide.pdf](http://www.rmspl.com.au/userguide/1x30_user_guide.pdf)
- Application: [http://www.rmspl.com.au/solutions/1x30\\_application.pdf](http://www.rmspl.com.au/solutions/1x30_application.pdf)
- Acad Case Drawings: <http://www.rmspl.com.au/1x30acad.htm>

## Test Certification

This is to certify that the equipment detailed below has been manufactured, inspected & tested in accordance with a Quality System which complies with the requirements of AS/NZS ISO9001-2000.

Order Number	Serial Number

Only valid when the "Passed" box has been signed off by Production Personnel.

## Version Control

Issue	Date	Summary of changes
A	24/03/2009	Initial issue.

Due to RMS continuous product improvement policy, this information is subject to change without notice.  
This document is uncontrolled and subject to copyright.

Author	Checked & Registered	.pdf file created	Released
DG	DHW	DG	



**1.0 HARDWARE SPECIFICATIONS – 1X050K02 [C][A][#][DST]**

**1.1 System Voltage**

[C] 48VDC

**1.2 Button & LED Colours**

[A] Open = Red Close = Green

**1.3 Custom Text**

[#] Specified at time of order.

**1.4 Options**

[DST] Steering Diodes, SC LED, Lamp Test.

**1.5 Non-Standard Features**

Hardware specifications not described in Technical Bulletin. None

**2.0 VERIFICATION**

This is to certify that the equipment has been manufactured, inspected and tested in accordance with a Quality System, which complies with the requirements of ISO9001: 2000.

Testing has been carried out against the declared performance specification 156-050-800 and in accordance with the relevant International (IEC) Standards.

PASSED BY	DATE

**3.0 CONNECTION DIAGRAM**

